

CF SERIES CARTRIDGE FILTER

Features

1. Compact and light weight
2. UV resistant tank
3. Heavy duty ring-lock lid allows easy cleaning and replacement of the cartridge element
4. Screw type air bleeder for easy removal of trapped air inside the filter tank
5. For domestic swimming pool & spa water body



ITEM- CODE	FILTER AREA(m ³)	VALVE CONNECTION	Max Flow Rate	A mm	B mm	C mm
OXY-CF-25	2.25	1" 50mm	92lpm 5.5m ³ /h	445	387	225
OXY-CF-50	4.63	1" 50mm	190lpm 11.4m ³ /h	625	567	225
OXY-CF-75	7.00	1" 50mm	283lpm 17.0m ³ /h	885	747	225
OXY-CF-100	9.40	2" 63mm	382lpm 22.9m ³ /h	985	927	225
OXY-CF-150	13.72	2" 63mm	555lpm 33.4m ³ /h	1165	1107	225
OXY-CF-200	16.82	2" 63mm	680lpm 40.9m ³ /h	1345	1287	225
OXY-SCF-25	2.25	1" 50mm	92lpm 5.5m ³ /h	411	400	225
OXY-SCF-50	4.63	1" 50mm	190lpm 11.4m ³ /h	591	580	225
OXY-SCF-75	7.00	1" 50mm	283lpm 17.0m ³ /h	771	760	225
OXY-SCF-100	9.40	2" 63mm	382lpm 22.9m ³ /h	951	940	225
OXY-SCF-150	13.72	2" 63mm	555lpm 33.4m ³ /h	1131	1120	225
OXY-SCF-200	16.82	2" 63mm	680lpm 40.9m ³ /h	1311	1300	225

